



ROAD TYPE	Reference Table 6C-1 (CA) Distance Between Signs**		
	A	B	C
Urban - 25 mph or less ***	100 feet	100 feet	100 feet
Urban - more than 25 mph to 40 mph ***	250 feet	250 feet	250 feet
Urban - more than 40 mph ***	350 feet	350 feet	350 feet
Rural	500 feet	500 feet	500 feet
Expressway / Freeway	1,000 feet	1,500 feet	2,640 feet

Speed* S (mph)	Reference Table 6C-3(CA). Minimum Taper Length ** for Width of Offset 12 feet (W)				
	Merging L (feet)	Shifting L/2 (feet)	Shoulder L/3 (feet)	Down Stream (feet)	Buffer*** (feet)
20	80	40	27	50-100	115
25	125	63	42	50-100	155
30	180	90	60	50-100	200
35	245	123	82	50-100	250
40	320	160	107	50-100	305
45	540	270	180	50-100	360
50	600	300	200	50-100	425
55	660	330	220	50-100	495
60	720	360	240	50-100	570
65	780	390	260	50-100	645
70	840	420	280	50-100	730
75	900	450	300	50-100	820

WORK HOURS:
7:00 AM- 5:00 PM

PLAN SHEET# 3

TCP 2

Adam Reed
(209) 628-0729
areed@rhyolitedevelopment.com

TRAFFIC CONTROL PLAN FOR:
2699 First St,
Atwater, CA 95301

PLAN PROVIDED BY:

 Construction, Engineering, Safety Supplies & Signs
 Sales Rentals Service
 1051 N. EMERALD AVE. MODESTO, CA 95351
 C31 LICENSED CONTRACTOR
 LICENSE NO. 788082

PLAN DRAWN BY:
ALBERTO DELGADO
TRAFFIC CONTROL SUPERVISOR

1-800-851-6262
209-522-8913

PROPOSED WORK SCHEDULE

TO BE DETERMINED

TYPE OF TRAFFIC CONTROL

Right Lane Clousres